



VS400PE-L

Output Power

| | | |
|---------------------|-----|-----|
| Standby Power (ESP) | kVA | 400 |
| | kW | 320 |
| Prime Power (PRP) | kVA | 356 |
| | kW | 284 |

Size

| | W x L x H (mm) | Weight (kg) | Fuel Tank (lt) | Noise dB(A) @ 7m |
|-----------|----------------|-------------|----------------|------------------|
| Canopied | 1650x5000x2250 | 4271 | 900 | 69 |
| Open Skid | 1650x3300x2050 | 3285 | 900 | N/A |

TBA: To Be Asked / N/A: Not Applicable

Continuous Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

Standby Power

The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 hrs of operation per year under average of 70% load. Overloading isn't permissible.

Prime Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Engine

| | | |
|------------------------------------|----------------------|-------------------------|
| Manufacturer | | PERKINS |
| Model | | 2206A-E13TAG2 |
| Cylinder Configuration | | INLINE |
| No of Cylinders | | 6 |
| Displacement | lt | 12,5 |
| Bore | mm | 130 |
| Stroke | mm | 157 |
| Compression Ratio | | 16,3:1 |
| Aspiration | | TURBOCHARGE-INTERCOOLER |
| Governor Type | | ELECTRONIC/ECM |
| Cooling System | | WATER |
| Coolant Capacity | lt | 51,4 |
| Lubrication Oil Capacity | lt | 40 |
| Electrical System | VDC | 24 |
| Speed / Frequency 50 Hz | rpm | 1500 rpm / 50 Hz |
| Engine Gross Power (Standby 50 Hz) | kW | 368,4 |
| Fuel Consumption %110 ESP 50 Hz | lt / h | 80 |
| Fuel Consumption %100 PRP 50 Hz | lt / h | 71 |
| Fuel Consumption %75 PRP 50 Hz | lt / h | 54 |
| Fuel Consumption %50 PRP 50 Hz | lt / h | 37 |
| Exhaust Outlet Temperature 50 Hz | °C | 630 |
| Exhaust Gas Flow 50 Hz | m ³ / min | 64,8 |
| Combustion Air Flow 50 Hz | m ³ / min | 23,6 |
| Cooling Air Flow 50 Hz | m ³ / min | 654 |

Alternator

| | | |
|-----------------------------------|-----|--|
| Manufacturer | | LEROY-SOMER |
| Model | | TAL046H |
| No of Phases | | 3 |
| Power Factor | | 0,8 |
| No of Bearings | | SINGLE |
| No of Poles | | 4 |
| No of Leads | | 6 |
| Voltage Regulation (Steady State) | | ± %1 |
| Insulation Class | | H |
| Degree of Protection | | IP 23 |
| Excitation System | | AVR (Automatic Voltage Regulator), Brushless |
| Connection Type | | STAR |
| Total Harmonic Content (No Load) | | < %2,5 |
| Frequency | Hz | 50 |
| Voltage Output 50 Hz | VAC | 230 / 400 |
| Rated Power (Standby) 400_50 Hz | kVA | 400 |
| Efficiency (4/4_400 V_50 Hz) | % | 93,1 |

509-T

Control Panel Features 509-T

- The 509-T is a next generation genset control unit combining multi-functionality and wide communication possibilities together with a reliable and low cost design.
- The unit complies and mostly exceeds world's tightest safety EMC, vibration and environmental standards for the industrial category.
- Software features are complete with easy firmware upgrade process through USB port. The Windows based PC software allows monitoring and programming through USB, RS-485, Ethernet and GPRS.
- The PC and server based Rainbow Scada software allows monitoring and control of an unlimited number of gensets from a single central location.



Functions

- AMF unit with uninterrupted transfer
- ATS unit with uninterrupted transfer
- Remote start controller
- Manual start controller
- Engine controller
- Remote display & control unit
- Wave form display of V & I
- Harmonic analysis of V & I
- CTs at genset or load side

Topologies

- 2 phase 3 wires, L1-L2
- 2 phase 3 wires, L1-L3
- 3 phase 3 wires, 3 CTs
- 3 phase 3 wires, 2 CTs (L1-L2)
- 3 phase 3 wires, 2 CTs (L1-L3)
- 3 phase 4 wires, star
- 3 phase 4 wires, delta
- 1 phase 2 wires

Communications

- SM-GPRS
- Web monitoring
- Web programming
- GSM-SMS
- e-mail
- USB Device
- RS-232
- J1939-CANBUS

- Technical information and values are according to ISO8528, ISO3046, NEMAMG-1.22, IEC600341, BS4999-5000, VDE0530 standards.
- Producing with ISO9001, ISO14001, OHSAS18001, CE standards.
- All information given in this leaflet is intended for general purposes only.

