



VS902PE-L

Output Power

Standby Power (ESP)	kVA	902
	kW	721
Prime Power (PRP)	kVA	808
	kW	646

Size

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise dB (A) @ 7m
Canopied	2200 x 5820 x 2435	7980	1650	87
Open Skid	1700 x 3800 x 2285	5827	1135	N/A

TBA: To Be Asked / N/A: Not Applicable

Continuous Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

Standby Power

The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 hrs of operation per year under average of 70% load. Overloading isn't permissible.

Prime Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Engine		
Manufacturer		PERKINS
Model		4006-23TAG3A
No of Cylinders		6
Cylinder Configuration		INLINE
Displacement	lt	22.921
Stroke	mm	190
Bore	mm	160
Compression Ratio		13,6:1
Aspiration		TURBOCHARGE-INTERCOOLER
Governor Type		ELECTRONIC
Cooling System		WATER
Coolant Capacity	lt	105
Lubrication Oil Capacity	lt	113,4
Electrical System	VDC	24
Speed / Frequency 50 Hz	rpm	1500 rpm / 50 Hz
Engine Gross Power (Standby 50 Hz)	kW	786
Fuel Consumption 110% (ESP 50 Hz)	lt/h	194
Fuel Consumption 100% (PRP 50 Hz)	lt/h	172
Fuel Consumption 75% (PRP 50 Hz)	lt/h	130
Fuel Consumption 50% (PRP 50 Hz)	lt/h	90
Exhaust Outlet Temperature 50 Hz	°C	500
Exhaust Gas Flow 50 Hz	m3/min	193
Combustion Air Flow 50 Hz	m3/min	73
Cooling Air Flow 50 Hz	m3/min	1200

Alternator		
Manufacturer		LEROY-SOMER
Model		TAL049E
No of Phases		3
Power Factor		0,8
No of Bearings		SINGLE
No of Poles		4
No of Leads		6
Voltage Regulation (Steady State)		± 1%
Insulation Class		H
Degree of Protection		IP 23
Excitation System		AVR (Automatic Voltage Regulator), Brushless
Connection Type		STAR
Total Harmonic Content (No Load)		< 3,5%
Frequency	Hz	50
Voltage Output 50 Hz	VAC	230 / 400
Rated Power (Standby) 400_50 Hz	kVA	1100
Rated Power (Continuous) 400_50 Hz	kVA	1000
Efficiency (4/4_400 V_50 Hz)	%	95,2